

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

Presents a revolutionary breakthrough
in lamination technology...the Fujipla
ALM 3220 Automatic Laminator



www.drylam.com
P: 888-633-1973
F: 866-473-0534
10908 Strang Line Rd.
Lenexa, KS 66215

Dry-Lam is taking lamination of On-Demand Digital Prints to a new level. With the Fujipla ALM 3220, laminating of Digital Prints has never been easier! The ALM 3220 will automatically feed, laminate and trim Digital Prints virtually unattended, freeing you to work on other profitable tasks. When coupled with our ASAP film, the ALM 3220 becomes an instant profit-generator for you! Get this amazing machine only from Dry-Lam, America's Leader in Digital On-Demand and Wide Format Printing Lamination.



SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

Presents a revolutionary breakthrough in lamination technology...the Fujipla ALM 3220 Automatic Laminator

ALM 3220 Automatic Laminator

- Small Foot Print – less than 3 sq. ft.
- Portable – locking roller casters
- 115 Volt, 15 amp service with economy mode
- Ultra quick warm up of less than 5 minutes
- Virtually Unattended Operation
- Digital Sheets sizes: 12"x18", 8.5"x11", 11"x17"
- Automatically feeds up to 200 sheets
- Laminates copy paper or as heavy as 130# cover stock
- Automatic two side lamination
- Automatic Flush or Sealed edge trim option
- 1 year parts and labor warranty

ALM 3220 Exclusive A.S.A.P. Roll Film

- Perfect for Digital Print technology
- Anti-static properties

ALM 3220 Exclusive A.S.A.P. Roll Film

1.5mil, 12.6" x 984 ft, Gloss	1.5mil, 12.6" x 984 ft, Matte
3.0mil, 12.6" x 492 ft, Gloss	3.0mil, 12.6" x 492 ft, Matte
5.0mil, 12.6" x 328 ft, Gloss	5.0mil, 12.6" x 328 ft, Matte
1.2mil, 12.6" x 984 ft, Nylon (One-sided application)	



ALM Specifications

Model	ALM3220
Laminating Speed	20"-48"/min.
Temperature Range	170-270°F
Ultra Fast Warm-Up Time	Approximately 5 minutes
Max Laminating Thickness	16mil
Film Thickness	1.2mil (One-sided application), 1.5mil, 3mil, 5mil A.S.A.P. Roll film
Thickness of Objects	3-10mil
Paper Feeding	Capacity: 200 Sheets, Skew-Free Feature, Paper Guide
Applicable Sizes	Letter Paper Size: 8½" x 11" With Margin: 8.74" x 11.24" Without Margin: 8.38" x 10.88" Tabloid Paper Size: 11" x 17" With Margin: 11.24" x 17.24" Without Margin: 10.88" x 16.88" Digital Paper Paper Size: 12" x 18" With Margin: 12.24" x 18.24" Without Margin: 11.88" x 17.88"
Trimming Methods	2 modes – Flush trim or edge seal for all 4 sides of the print
Operation Panel	LCD display for start, stop, temperature, speed, and trim settings
Other Features	Laminated sheet counter, Film tension control, Roller gap lever, Paper thickness adjustment lever, Automatic stop at end of film, Power saving mode, Emergency stop function
Power Consumption	900W
Power Supply	AC 120V (60Hz)
Net Weight	Laminator: 110 Lbs. Stand: 48.5 Lbs.
Included Accessories	Stand with film waste box, Printed operations manual and CD

www.drylam.com

P: 888-633-1973

F: 866-473-0534

10908 Strang Line Rd.

Lenexa, KS 66215

Distributed by: